

Stress plate HTV-82/40 F



Cross references

Dabo® SW 8 RT-4.8
 Dabo® TKR-4.8
 Dabo® TKE-4.8
 Dabo® TKR-4-4.8
 Dabo® TKR-ZT6-5.5
 Dabo® VHT-R-4.8
 Dabo® VHT-E-4.8
 Concrete screw FBS-R
 Aerated concrete screw FPS-E

Application range

- > To fix roofing membrane insulating material to substructures made of timber, wood-based materials, concrete and aerated concrete
- > For solid substrate


Properties

- > Alu-zinc-coated steel

Note

Compatible with EJOT Dabo® screws / with concrete and aerated concrete screws

Applications



Certifications



Product online



Order description	Width [mm]	Length [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
HTV-82/40 F	40	82	500		3020093401	4061245012506

Compatibility acc. to ETA-07/0013

	SW 8 RT-4.8	SW 8 ET-4.8	TKR-4.8	TKE-4.8	TKR-4-4.8	TKR-ZT6-5.5	VHT-R-4.8	VHT-E-4.8	JT2-ST-2-6.0	JT2-ST-2-6.8	JT3-ST-2-6.0	FBS-R-6.3	JBS-R-7.5	FPS-E-8.0	SDF-S-10H-E	SDP-S-10G-E
HTV 82/40 F	X		X	X	X	X	X	X				X		X		