

## Self-drilling screw JT4-3H/5-5.5x19

## Self-drilling screw JT9-3H/5-5.5x19



## Cross references

Socket wrench insert AF8  
Cordless screwdriver ASCS 6.3

## Application range

- > To form sliding and fixed points on substructures of rear-ventilated facades
- > Fastening pre-drilled stainless steel or aluminium wall brackets to aluminium support profiles
- > For component assemblies from 3.1 – 5.0 mm (component I + component II)

## Properties

- > A2 or A4 stainless steel

## Note

Component assemblies checked with  $R_m$  (component II)  $\geq 190$ ,  $\geq 215$  and  $\geq 245$  N/mm<sup>2</sup>. For bearing values, please refer to the national test certificate (abP) P-BWU02-1980001.


## Possible part combinations

Component I [mm]	Component II [mm]	$R_m$ support profile/ Wall bracket
	1.6	
1.5 (stainless steel)	2.0	$\geq 190$ N/mm <sup>2</sup>
	2.4	(aluminium)
3.0 (aluminium)	1.6	
	2.0	

## Applications



## Technical data



## Certifications



## Product online



Order description	Length [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
<b>JT4 made of A2 stainless steel</b>					
JT4-3H/5-5.5x19	19	500		7380540300	4061245014289
JT4-3H/5-5.5x19 VE100	19	100		6380540300	4061245014876

## Product online



Order description	Length [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
<b>JT9 made of A4 stainless steel</b>					
JT9-3H/5-5.5x19	19	500		7380540340	4061245014272
JT9-3H/5-5.5x19 VE100	19	100		6380540340	4061245014869