

NEW T-FAST® wood screw JW4 wafer head**Application range**



- > Fastening of non-pre-drilled or pre-drilled components made of wood, wood-based material and pre-drilled and pre-set steel components to non-pre-drilled or pre-drilled components made of solid wood, solid structural timber (KVH), glued-laminated timber (BSH), solid wood panels, laminated veneer lumber (LVL), wood-based panels or cross-laminated timber
- > For weathered areas
- > Suitable for universal application

Characteristics

- > Stainless steel CRC II or stainless steel A2 with dry lubricant
- > Wafer head (STS) for strong tightening during installation and increased holding forces after installation
- > Full and partial thread
- > Optimised thread geometry for improved prevention of screw over-tightening with short screws and accelerated processing with long screws
- > T-FAST® Plus point geometry facilitates the screwing-in process through quick point biting, low screwing-in torque and efficiently reduced wood splitting

Cross references

Cordless screwdriver ASCS QSW
Bit hexalobular TX

**Applications****Technical specifications****Certifications****Product online**

Order description	d [mm]	l [mm]	l _g [mm]	d _h [mm]	Drive	PU [pieces]	Price/100 [EUR]	Article number	EAN
d 6.0 – full-threaded screw									
JW4-2-Plus-STS-6.0x40/35 S TX30	6.0	40	35	14.0	TX30	100		3820000483	4061245123905
JW4-2-Plus-STS-6.0x60/52 S TX30	6.0	60	52	14.0	TX30	100		3820000484	4061245123912
JW4-2-Plus-STS-6.0x80/70 S TX30	6.0	80	70	14.0	TX30	100		3820000485	4061245123929
d 6.0 – partial threaded screw									
JW4-2-Plus-STS-6.0x100/80 S TX30	6.0	100	80	14.0	TX30	100		3820000486	4061245123936
d 8.0 – full-threaded screw									
JW4-2-Plus-STS-8.0x60/50 M TX40	8.0	60	50	21.0	TX40	50		3820000487	4061245123943
JW4-2-Plus-STS-8.0x80/70 M TX40	8.0	70	70	21.0	TX40	50		3820000440	4061245123950
d 8.0 – partial threaded screw									
JW4-2-Plus-STS-8.0x100/80 M TX40	8.0	100	80	21.0	TX40	50		3820000446	4061245123967
JW4-2-Plus-STS-8.0x120/80 M TX40	8.0	120	80	21.0	TX40	50		3820000455	4061245123974