

EJOT® SAPHIR self-drilling screw JT2-FZ-F-6,5

Fastening corrugated fibre cement sheet
to timber substructure

www.ejot.es

EJOT®

Self-drilling screws JF2/JT2

Case-hardened steel, zinc-plated

EJOT®

EJOT® SAPHIR self-drilling screw JT2-FZ-F-6.5

Ø [mm]	Length [mm]	PU	Price/100 [EUR]	Order description	Article number
FZD sealing washer					
6.5	100	100		JT2-FZ-F-6.5x100-FZD*	3 515 175 608
6.5	130	100		JT2-FZ-F-6.5x130-FZD	3 515 675 608
6.5	180	50		JT2-FZ-F-6.5x180-FZD*	3 518 075 608

*no approval

Application area

- Fastening corrugated fibre cement sheet to timber substructure

Properties

- Case-hardened steel, hot-dip zinc-plated
- Pre-assembled FZD sealing washer
- A2 stainless steel washer
- Screw wings save additional drilling into the corrugated slabs
- Reduced forcing tension

Note

Suitable for corrugation 5 when covering with corrugated fibre cement sheet 177/51 to timber substructure without insulation. For the dimensioning and the use of fastening materials please note the manufacturer's instructions for use as well as the national approvals.


Technical Data

Drive	Hexagon AF8
-------	-------------

WWW.AUSSCHREIBEN.DE



AF8



Approval
Z-31.4-174

Cross reference

Accessories
Metal screwdriver SCS 6.3-SH2
JT4-FZ-6.5

Allgemeine bauaufsichtliche Zulassung
Nr. Z-31.4-174 vom 23. November 2012

Deutsches
Institut
für
Bautechnik

	<p>Bild 10:</p> <p>EJOT JT2-FZ-6,5 x L für Holzunterkonstruktion</p> <p>Pos.1 Befestiger Werkstoff: Einsatzgehärteter Kohlenstoffstahl Werkstoffangaben beim DIBt hinterlegt Oberfläche feuerverzinkt min. 50 µm</p> <p>Pos. 2 Dichtscheibe Ø 22 mm, t = 1,2 mm Werkstoff: nichtrostender Stahl, Werkstoff-Nr. 1.4301 (nach DIN 17440)</p> <p>Pos. 3 Dichtpilz Ø 25 mm Werkstoff: Elastomer EPDM, 60° Shore A, schwarz</p> <p>Einschraubtiefe $s_w \geq 50$ mm</p>
	<p>Bild 11:</p> <p>EJOT JT4-FZ-6,5 x L für Holzunterkonstruktion</p> <p>Pos.1 Befestiger Werkstoff: nichtrostender Stahl, Werkstoff-Nr. 1.4301 (nach DIN 17440) Werkstoffangaben beim DIBt hinterlegt</p> <p>Pos. 2 Dichtscheibe Ø 22 mm, t = 1,2 mm Werkstoff: nichtrostender Stahl, Werkstoff-Nr. 1.4301 (nach DIN 17440)</p> <p>Pos. 3 Dichtpilz Ø 25 mm Werkstoff: Elastomer EPDM, 60° Shore A, schwarz</p> <p>Einschraubtiefe $s_w \geq 50$ mm</p>
<p>Maße in mm, ohne Maßstab</p>	
<p>Faserzement-Wellplatten "Eternit Wellplatte" Profil P5, P6 und P6¾ mit Polypropylen-Bandeinlagen nach DIN EN 494</p> <p>Geometrie und Materialzusammensetzung der Befestiger EJOT JT2-FZ-F-6,5xL bzw. EJOT JT4-FZ-F-6,5xL</p>	<p>Anlage 1 Blatt 4 von 12</p>