

EJOT[®] stainless steel SAPHIR self-drilling screw JT4-FR-2H/6-4.8

Fastener for ALUCOBOND[®] external wall cladding
according to Z-33.2-6

Self-drilling screws JT4/JT9

A2/A4 stainless steel



EJOT® stainless steel SAPHIR self-drilling screw JT4-FR-2H/6-4.8

with centring bush

Ø [mm]	Length [mm]	Clamp thickness [mm]	PU	Price/100 [EUR]	Order description	Article number
Self-drilling screw						
4.8	22	6	500		JT4-FR-2H/6-4.8x22*	7 384 170 300
Centring bush						
-	-	-	500		Centring bush	3 010 003 700

*JT9 made of A4 stainless steel, upon request

Application Range

- Fastener for ALUCOBOND® external wall cladding according to Z-33.2-6

Properties

- A2 stainless steel
- Fastener heads in ALUCOBOND® standard and special colours available (delivery time ca. 10 work days)

Advantages



- Centred drilling and simultaneous fastening of the boards to the substructure
- No pre-drilling of the substructure

Note

We recommend the tapered special bit TORX® T25W-1/4"/Cx25 for force fit in the fastener head.

Technical Data

Drilling capacity $t_1 + t_2$	1.0 + 3.0 mm
Drive	Hexalobular drive T25
Ø drill hole centring bush	8.0 mm



Cross reference

Accessories
Bit Torx®
Metal screwdriver SCS 6.3