

## **EJOT<sup>®</sup> stainless steel SAPHIR self-drilling screw JT4-LT-2/6-6.0x25**

Fastening facade panels to aluminium substructure  $\leq 2.0$  mm

[www.ejot.es](http://www.ejot.es)

**EJOT<sup>®</sup>**

# Self-drilling screws JT4/JT9

A2/A4 stainless steel



## EJOT® stainless steel SAPHIR self-drilling screw JT4-LT-2/6-6.0x25

Ø [mm]	Length [mm]	max. panel thickness [mm]	PU	Price/100 [EUR]	Order description	Article number
6.0	25	10	500		JT4-LT-2/6-6.0x25	7 384 199 300

NOTE: Also available in RAL lacquering

### Application area


- Fastening facade panels to aluminium sub-structure ≤ 2.0 mm

### Properties

- A2 stainless steel
- Pan head

### Technical Data

Drilling capacity (t <sub>i</sub> pre-drilled) + t <sub>II</sub>	1.5-2.0 mm
Drive	Hexalobular drive T25
Head diameter	16 mm
Head height	2 mm
Length non-threaded part	6.0 mm



### Cross reference

Accessories  
TORX T25W-1/4"/Cx25

Minimum tensile strength	
Ø mm	kN
6.0	12.1

Minimum shear strength	
Ø mm	kN
6.0	10.2