

EJOT® SAPHIR self-drilling screw JT2-FZ-6-6.3

Fastening corrugated fibre cement sheet 177/51
to steel substructure 1.5-6 mm

www.ejot.es

EJOT®

Self-drilling screws JF2/JT2

Case-hardened steel, zinc-plated

EJOT®

EJOT® SAPHIR self-drilling screw JT2-FZ-6-6.3

Ø [mm]	Length [mm]	PU	Price/100 [EUR]	Order description	Article number
FZD sealing washer					
6.3	110	100		JT2-FZ-6-6.3x110-FZD	3 512 275 664
6.3	155	50		JT2-FZ-6-6.3x155-FZD	3 513 075 664
Order information: Further lengths upon request.					

Application area

- Fastening corrugated fibre cement sheet 177/51 to steel substructure 1.5–6 mm

Properties

- Case-hardened steel
- Climadur coated – high-quality coating to improve corrosion protection (15 Kesternich cycles, DIN 50018, 1997)
- Pre-assembled FZD sealing washer
- A2 stainless steel washer
- Screw wings save additional drilling into the corrugated slabs
- Reduced forcing tension

Note

For the dimensioning and the use of fastening materials please note the manufacturers instructions for use as well as the national approvals.


Technical Data

Drive	Hexagon AF8
-------	-------------

WWW.AUSSCHREIBEN.DE



AF8



Cross reference

Accessories
Metal screwdriver SCS 6.3-SH2